



ClearCoat

A pure acrylic copolymer emulsion designed for use as an exterior and interior surface coating application.

Applied Uses

- Sprayed wet or dry
- Sprayed before and after curing
- Brush applied

Benefits

- Can be applied "wet" or "dry" and tailored to suit your production needs
- Enhanced drying times
- Hydrophobicity
- Surface Pore Blocker
- Efflorescence Control
- Low Viscosity for ease of Spraying and Pumping
- Colour Enhancement
- Weather Resistant Properties
- Gloss Finish at various dosages

Specification Parameters *

Solids content: 18-22%	pH: $\geq 8.0 \leq 9.0$
Viscosity at 25 Degrees Celsius (Brookfield RV8, Spindle 2, 100 rpm): $\geq 0.00 \leq 150$	Specific Gravity: 1.01 – 1.03
	Tg: 6

* Not to be taken as a batch specification

Applications

- Decorative concrete products
- Concrete and Clay Roof Tiles
- Natural Stone
- Concrete and Clay Brick

Product Packaging

Available in bulk, 1,000 litre IBCs, 210 litre drums and 25 litre jerry cans.

Product Storage & Shelf Life

ClearCoat should be stored in the original, unopened and undamaged containers in a dry place at temperatures between 5°C and 30°C. Protect from frost and extended exposure to direct sunlight.

For Industrial Use Only. Not for internal consumption.
Consult SDS for safety and regulatory information.

PDS - CLEARCOAT - 06/2022

Excelsior Works Castle Park Flint Flintshire CH6 5NT United Kingdom
 T +44 (0) 1352 732 157 F +44 (0) 1352 735 530 E info@procterjohnson.com
procterjohnson.com



The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.