



# KreteControl 205

A non-swipe producing admixture designed to offer integral water repellency and both primary and secondary efflorescence control in precast concrete products at low dosage rates.

## Features

- Water Repellency
- Efflorescence Control

## Benefits

- Minimizes Water Penetration/Absorption
- Improves Service Life of CMUs
- Improves Aesthetic Appearance of CMUs
- Promotes and Maintains Brighter Colours

## Technical Information

PARAMETER	TYPICAL VALUE
Appearance	Amber Liquid
Specific Gravity	0.890

## Directions for use

1. For Efflorescence Control: Use at dosage rate of 200 – 350ml per 100kg of cementitious material.
2. Add after the introduction of the pre-wet aggregates.
3. Mix for 90 seconds after addition of admixture.
4. Check the moisture content of the mix and add additional water if needed.

## Product packaging

- Available in bulk, 1,000 litre IBCs, 210 litre drums and 25 litre jerry cans.
- Samples are available by request.

## Product storage and shelf life

- Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>35 C°). KEEP FROM FREEZING.
- Avoid physical damage to containers.
- Krete Control 202 has a shelf life of eight (8) months in original, unopened packaging.

For Industrial Use Only. Not for internal consumption.  
Consult SDS for safety and regulatory information.

PDS – KRETECONTROL 205 – 06/2022

Excelsior Works Castle Park Flint Flintshire CH6 5NT United Kingdom  
T +44 (0) 1352 732 157 F +44 (0) 1352 735 530 E info@procterjohnson.com  
[procterjohnson.com](http://procterjohnson.com)



The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.