



KreteMix 110

An aqueous admixture designed to offer plasticizing action while allowing increased water use in semi dry concrete products.

Features

- Plasticizing Action
- Allows Increased Water Use

Benefits

- Improves Batch Consistency
- Decreases Machine Feed Time
- Improves Green Strength
- Improves Finish Texture
- Effectively Hydrates Cement
- Improves Compressive Strength

Technical Information

PARAMETER	TYPICAL VALUE
Appearance	Clear Blue Liquid
Specific Gravity	1.032
pH	8.5

Directions for use

1. Use at dosage rate of 35 – 130ml per 100kg of cementitious material.
2. Add after the main portion of batch water.
3. Mix for 60 seconds after addition of admixture.

Product packaging

- Available in bulk, 1,000 litre IBCs, 210 litre drums and 25 litre jerry cans.
- Samples are available by request.

Product storage and shelf life

- Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>35 C°). KEEP FROM FREEZING.
- Avoid physical damage to containers.
- Krete Mix 110 has a shelf life of eight (8) months in original, unopened packaging.

For Industrial Use Only. Not for internal consumption.
Consult SDS for safety and regulatory information.

PDS – KRETEMIX 110 – 06/2022

Excelsior Works Castle Park Flint Flintshire CH6 5NT United Kingdom
 T +44 (0) 1352 732 157 F +44 (0) 1352 735 530 E info@procterjohnson.com
procterjohnson.com



The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.