



KreteSuperPlast 710

A high performance concrete admixture designed to offer superior plasticizing action, mid-range water reduction, and densification in precast concrete products.

Features

- Plasticizing Action
- Mid to High Range Water Reduction (15–25% Reduction)
- Densification

Benefits

- Improves Batch Consistency
- Improves Green Strength
- Improves Surface Texture
- Allows Mix to Compact Readily
- Little to No Vibration Needed
- Provides Sharp Corners and Edges

Technical Information

PARAMETER	TYPICAL VALUE
Appearance	Brown Liquid
Specific Gravity	1.055
pH	6.5

Directions for use

1. Use 1/3 less water per batch when using KreteSuperPlast 710.
2. Use at dosage rate of 175 – 1000ml per 100kg cementitious material.
3. Add after introduction of pre-wet aggregates.
4. Check air content.

Note: Dosage rate will vary depending on mix design.

Product packaging

- Available in bulk, 1,000 litre IBCs, 210 litre drums and 25 litre jerry cans
- Samples are available by request.

Product storage and shelf life

- Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>35 C°). KEEP FROM FREEZING.
- Avoid physical damage to containers.
- KreteSuperPlast 710 has a shelf life of eight (8) months in original, unopened packaging.