



KreteXcel 500

A concentrated, non-chloride cement hydration accelerator for precast concrete products.

Features

- Highly Concentrated
- Accelerates Concrete Curing
- Formulated for Precast Applications
- Non-Chloride

Benefits

- Reduces Curing Costs
- Provides High Early Strength
- Improves Cold Water Curing
- Improves Cold Weather Curing

Technical Information

PARAMETER	TYPICAL VALUE
Appearance	Clear Liquid
Specific Gravity	1.370
pH	5.5

Directions for use

1. Use at dosage rate of 250 – 1000ml per 100kg of cementitious material.
2. Add with the final batch water.
3. For Ribbon Mixers: Mix for 60 seconds after addition of admixture.
For Pan Mixers: Mix for 30 seconds after addition of admixture.

Product packaging

- Available in bulk, 1,000 litre IBCs, 210 litre drums and 25 litre jerry cans
- Samples are available by request.

Product storage and shelf life

- Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>35 C°). KEEP FROM FREEZING.
- Avoid physical damage to containers.
- Krete Xcel 500 has a shelf life of eight (8) months in original, unopened packaging.

For Industrial Use Only. Not for internal consumption.
Consult SDS for safety and regulatory information.

PDS – KRETXCCEL 500 – 06/2022

Excelsior Works Castle Park Flint Flintshire CH6 5NT United Kingdom
 T +44 (0) 1352 732 157 F +44 (0) 1352 735 530 E info@procterjohnson.com
procterjohnson.com



The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.