



# KreteXcel 510

A non-chloride admixture designed to provide plasticising action, hardening and cure acceleration in concrete products.

## Features

- Highly Concentrated
- Accelerates Concrete Curing
- Plasticizing Action
- Non-Chloride

## Benefits

- Reduces Curing Costs
- Provides High Early Strength
- Improves Cold Water Curing
- Improves Batch Consistency
- Decreases Machine Feed Time
- Improves Finish Texture
- Improves Cold Weather Curing

## Technical Information

PARAMETER	TYPICAL VALUE
Appearance	Clear Pale Green Liquid
Specific Gravity	1.130
pH	11

## Directions for use

1. Use at dosage rate of 130 – 650ml per 100kg of cementitious material.
2. Add with the final batch water.
3. For Ribbon Mixers: Mix for 60 seconds after addition of admixture.  
For Pan Mixers: Mix for 30 seconds after addition of admixture.

## Product packaging

- Available in bulk, 1,000 litre IBCs, 210 litre drums and 25 litre jerry cans
- Samples are available by request.

## Product storage and shelf life

- Store in dry area. Keep containers tightly closed. Do not store in excessively high temperatures (>35 C°). KEEP FROM FREEZING.
- Avoid physical damage to containers.
- Krete Xcel 510 has a shelf life of eight (8) months in original, unopened packaging.

For Industrial Use Only. Not for internal consumption.  
Consult SDS for safety and regulatory information.

PDS – KRETXCCEL 510 – 06/2022

Excelsior Works Castle Park Flint Flintshire CH6 5NT United Kingdom  
 T +44 (0) 1352 732 157 F +44 (0) 1352 735 530 E info@procterjohnson.com  
[procterjohnson.com](http://procterjohnson.com)



The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.