

∞TilePrem Plus

A VOC Free mineral based Form Oil specially formulated for the concrete roof tile industry to ensure early mould release once the concrete has set.

Features

- Specially formulated for the roof tile industry
- Ready to use product
- Will not clog fine jets
- VOC Free

Benefits

- Consumption reduction in grams per roof tile pallet vs self-blended oils
- Temporarily protects metallic moulds from corrosion and extends the life of the mould
- Does not stain or affect the colour of the concrete
- Does not affect the adhesion of subsequent finishes and coatings
- Does not modify cement hydration

Technical Information

PARAMETER	TYPICAL VALUE
Appearance	Translucent Amber
	Liquid
Specific Gravity	0.80 – 0.90

Directions for use

Before application

- 1. Pallet must be stripped and cleaned of concrete and oil deposits.
- 2. TilePrem Plus is usually applied by an in line high pressure oil sprayer or in line brush applicator.

After application

Avoid excessive application.

Product Packaging

Available in bulk, 1,000 litre IBCs, 210 litre drums and 25 litre jerry cans.

Product Storage & Shelf Life

TilePrem Plus has a shelf life of 8 months in original, unopened packaging. Store between 5°C and 25°C away from direct sunlight. Viscosity will vary with temperature.

For Industrial Use Only. Not for internal consumption. Consult SDS for safety and regulatory information.

Excelsior Works Castle Park Flint Flintshire CH6 5NT United Kingdom T +44 (0) 1352 732 157 F +44 (0) 1352 735 530 E info@procterjohnson.com procterjohnson.com PDS - TILEPREMPLUS - 06/2022



The information presented above is true and accurate to the best of our knowledge. No warranty or guarantee, expressed or implied is made regarding the performance of the product. This information is not intended to be all-inclusive concerning handling, storage and use of the product. Health and other regulatory factors are the responsibility of the customer.